

Leather Details:

Bovine of European origin, lightly buffed natural grain.

Thickness 1,2 - 1,4 mm.

Chrome tanning.

The average size of each hide is 4,8 - 5,0 m².

Full dyed and finished with resins and pigments.

Article with a pigmented and protective coat, with a soft, waxy feel and semi-matt appearance.

Test / Test Method	Measurement Unit	Guaranteed
Colour fastness to and for rubbing Dry (UNI EN ISO 11640) Wet (UNI EN ISO 11640)	ISO 105 A03	> = 4 > = 3/4
Sweat Alkaline Solution Sweat (ISO 11641 pH 8)		> = 3/4
Colour fastness to artificial Xenon light (UNI EN ISO 105 B02)	Blue Scale	> = 5
Finish Adhesion (ISO 11644)	N/Cm	> = 2,5
Flexing Endurance (ISO 5402)	Cycles	> = 50.000
Determination of pH (ISO 4045)	pH	> = 3,5
Difference figure (only for pH < 4)		< = 0,7
Tear strenght - Single edge tear (ISO 3377-1)	N	> = 20

Maintenance & Cleaning:

For a normal cleaning we suggest dusting with a soft dry cloth.

It is forbidden to use abrasive or aggressive products such as solvents and stain removers.

Avoid placing the leather in direct sun light.

Do not use steam.

Do not use shoe products.

